

Representative image only. Some models may vary in appearance. Due to continuous product improvement, specifications are subject to change without notice.



For complete warranty details visit www.AspenMfg.com

Product Features and Specifications

- Rifled copper tubing, enhanced aluminum fins.
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed.
- Left- or right-hand refrigerant and plumbing connections.
- Liquid line - 3/8" ODS, suction line - 1/4" ODS on 1-1/2- 3 ton and 7/8" ODS on 3-1/2 - 5 ton. •Externally mounted flowrator body with Schrader valve for hiss-testing.
- Heavy duty plastic drain pans on most models.
- Upflow without field modification. Downflow applications require plate kit, not included.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with both R-22 and R-410A when proper metering device is used.
- Ten-year limited warranty.

CUSTOMIZATION

- Factory or field-installable TXV
- Powder painted stainless steel drain pan.
- Schrader mounted on suction manifold.

COIL MODEL	NOMINAL CAPACITY (BTUs)	FLOW RATOR SIZE		DIMENSIONS						SHIPPING INFORMATION				
				PAN WIDTHS (W)"				PAN DEPTH (D)"	BARE SLAB HEIGHT (H)"	SHIPPING WEIGHT (LBS)			SKID QTY	
				R-22	R-410A	13	16			19-1/2	23	2 ROW		3 ROW
CA24A*	24,000	0.059	0.055	13	16	19-1/2		19-3/8	13-1/2	17	27	35	30	
CA24B*		0.059	0.055	13	16	19-1/2		19-3/8	15-1/2	20	31	41	25	
CA24C*		0.059	0.055	13	16	19-1/2		19-3/8	17-1/2	23	36	47	25	
CA24D*		0.059	0.055	13	16	19-1/2		19-3/8	19-1/2	25	40	53	20	
CA30A*	30,000	0.068	0.059	13	16	19-1/2		19-3/8	15-1/2	20	31	41	25	
CA30B*		0.068	0.059	13	16	19-1/2		19-3/8	17-1/2	23	36	47	25	
CA30C*		0.068	0.059	13	16	19-1/2		19-3/8	19-1/2	25	40	53	20	
CA30D*		0.068	0.059	13	16	19-1/2		19-3/8	21-1/2	28	45	58	16	
CA30E*		0.068	0.059	13	16	19-1/2		19-3/8	21-1/2	30	47	60	16	
CA36A*	36,000	0.074	0.068	13 for 2, 3R; 16 for 4R	16	19-1/2		19-3/8	17-1/2	23	36	47	25	
CA36B*		0.074	0.068	13 for 2, 3R; 16 for 4R	16	19-1/2		19-3/8	19-1/2	25	40	53	20	
CA36C*		0.074	0.068	13 for 2, 3R; 16 for 4R	16	19-1/2		19-3/8	21-1/2	28	45	58	16	
CA36D*		0.074	0.068	13 for 2, 3R; 16 for 4R	16	19-1/2		19-3/8	23-1/2	31	49	64	12	
CA42A*	42,000	0.080	0.074		16	19-1/2	23	19-3/8	19-1/2	25	40	53	20	
CA42B*		0.080	0.074		16	19-1/2	23	19-3/8	21-1/2	28	45	58	16	
CA42C*		0.080	0.074		16	19-1/2	23	19-3/8	23-1/2	31	49	64	12	
CA42D*		0.080	0.074		16	19-1/2	23	19-3/8	25-1/2	34	54	70	12	
CA48A*	48,000	0.084	0.080		16	19-1/2	23	19-3/8	21-1/2	28	45	58	16	
CA48B*		0.084	0.080		16	19-1/2	23	19-3/8	23-1/2	31	49	64	12	
CA48C*		0.084	0.080		16	19-1/2	23	19-3/8	25-1/2	34	54	70	12	
CA48D*		0.084	0.080		16	19-1/2	23	19-3/8	27-1/2	37	58	76	12	
CA48F*		0.084	0.080		16	19-1/2	23	19-3/8	25-1/2	36	56	72	12	
CA48G*		0.084	0.080		16	19-1/2	23	19-3/8	27-1/2	39	60	78	12	
CA60A*	60,000	0.092	0.089			19-1/2	23	19-3/8	25-1/2	34	54	70	12	
CA60B*		0.092	0.089			19-1/2	23	19-3/8	27-1/2	37	58	76	12	
CA60C*		0.092	0.089				19-1/2 (2)	23 (2)	21-3/4	24-1/2	38	60	79	12
CA60D*		0.092	0.089				19-1/2 (2)	23 (2)	21-3/4	26-1/2	41	65	86	12
CA60E*		0.092	0.089					24 (3)	21	26-1/2	46	73	95	12
CA60F*		0.092	0.089				19-1/2	23	19-3/8	25-1/2	41	62	80	12
CA60G*		0.092	0.089					24 (3)	21	26-1/2	48	75	97	12

Notes: 1) Do not use heavy duty polypropylene drain pans on oil furnaces or other applications where outlet temperatures may exceed 290°F +/-5°F. Specify metal drain pans for these applications. 2) Metal drain pan. 3) Metal drain pan. Slab rotated 90°. Refrigerant and plumbing connections still exit in front. 4) Only metal drain pans are available for 13" and 16" wide 4 row coils.

to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.






Revised 2-7-24.
In keeping with its commitment
©2024

CA SERIES

UNCASED UPFLOW/DOWNFLOW COILS

 P 800-423-9007